

## SharXS HTI

双端金卤灯



### 应用领域


- Concert and effect lighting

### 产品特点

- High thermal load capacity thanks to eXtreme Seal (XS) technology - enables high pinch temperatures of up to 450 °C
- 热启动功能



## 产品系列数据表



---

46860\_SharXS HTI

## 产品系列数据表

### 技术参数

产品描述	电参数			光度数据		
	标称电压	启动电压	标称电流	标称光通量	亮度	色温
SHARXS HTI 400 W/D3/75 <sup>1)</sup>	50.0 V	3.0 / 25 kVp <sup>5)</sup>	85 安培	26000 lm	55000 cd/cm <sup>2</sup>	7500 K
SHARXS HTI 700 W/D4/60 <sup>2)</sup>	70.0 V	3.0 / 25 kVp <sup>5)</sup>	1100 安培	59000 lm	60000 cd/cm <sup>2</sup>	6000 K
SHARXS HTI 700 W/D4/75 <sup>3)</sup>	70.0 V	3.0 / 25 kVp <sup>5)</sup>	10 安培	59000 lm	60000 cd/cm <sup>2</sup>	7500 K
SHARXS HTI 1200 W/D7/60 <sup>3)</sup>	96.6 V	5.0 / 35 kVp	12.4 安培	110000 lm	41000 cd/cm <sup>2</sup>	6900 K
SHARXS HTI 1200 W/D7/75 <sup>2)</sup>	95.3 V	5.0 / 35 kVp	12.6 安培	91000 lm	41000 cd/cm <sup>2</sup>	8800 K
SHARXS HTI 1500 W/D7/60 <sup>4)</sup>	110 V	5.0 / 35 kVp	136 安培	145000 lm	42000 cd/cm <sup>2</sup>	6000 K

产品描述	显色指数 Ra	发光效率	尺寸和重量			温度	寿命
			直径	长度	光中心 (LCL)	反射罩窄口最大允许温度	寿命
SHARXS HTI 400 W/D3/75 <sup>1)</sup>	80		18.0 mm	136.0 mm	57.5 mm	450 °C	750 h
SHARXS HTI 700 W/D4/60 <sup>2)</sup>	>80	85 lm/W	18.0 mm	136.0 mm	57.5 mm	450 °C	750 h
SHARXS HTI 700 W/D4/75 <sup>3)</sup>	>80		21.0 mm	136.0 mm	57.5 mm	450 °C	750 h
SHARXS HTI 1200 W/D7/60 <sup>3)</sup>	85		21.0 mm	136.0 mm	57.5 mm	450 °C	750 h
SHARXS HTI 1200 W/D7/75 <sup>2)</sup>	80	90 lm/W	21.0 mm	136.0 mm	57.5 mm	450 °C	750 h
SHARXS HTI 1500 W/D7/60 <sup>4)</sup>	>80		24.5 mm	136.0 mm	57.5 mm	450 °C	750 h

产品描述	更多的产品数据	功能	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
	灯头 (标准名称)	燃点位置	Date of Declaration	Primary Article Identifier
SHARXS HTI 400 W/D3/75 <sup>1)</sup>	SFc10-4	任意	05-03-2024	4008321911353   4008321285157
SHARXS HTI 700 W/D4/60 <sup>2)</sup>	SFc10-4	任意	05-03-2024	4008321285218
SHARXS HTI 700 W/D4/75 <sup>3)</sup>	SFc10-4	任意	05-03-2024	4008321285232
SHARXS HTI 1200 W/D7/60 <sup>3)</sup>	SFc10-4	任意	05-03-2024	4050300854663   4008321285256
SHARXS HTI 1200 W/D7/75 <sup>2)</sup>	SFc10-4	任意	05-03-2024	4008321285270
SHARXS HTI 1500 W/D7/60 <sup>4)</sup>	SFc10-4	任意	05-03-2024	4008321285294   4008321349569

产品描述	Candidate List Substance 1	Declaration No. in SCIP database
SHARXS HTI 400 W/D3/75 <sup>1)</sup>	No declarable substances contained	In work
SHARXS HTI 700 W/D4/60 <sup>2)</sup>	No declarable substances contained	No declarable substances contained
SHARXS HTI 700 W/D4/75 <sup>3)</sup>	No declarable substances contained	No declarable substances contained

## 产品系列数据表

产品描述	Candidate List Substance 1	Declaration No. in SCIP database
SHARXS HTI 1200 W/D7/60 <sup>3)</sup>	No declarable substances contained	In work
SHARXS HTI 1200 W/D7/75 <sup>2)</sup>	No declarable substances contained	No declarable substances contained
SHARXS HTI 1500 W/D7/60 <sup>4)</sup>	No declarable substances contained	In work

<sup>1)</sup> 无滚花螺母的30单位/箱OEM包装产品可供选择

<sup>2)</sup> XS = 极端密封 (最大允许温度为450 °C)

<sup>3)</sup> 无滚花螺母的30单位/箱OEM包装产品可供选择/XS = 极端密封 (最大允许温度为450 °C)

<sup>4)</sup> 可运行在1200...1500 W之间

<sup>5)</sup> 冷

## 产品系列数据表

---

### 安全建议

Because of their high luminance, UV radiation and high internal pressure during operation, SharXS lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

### 应用建议

更多详细应用信息和图形,请参阅产品数据表。

### 免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。