

XBO 4000 W/DHP LL OFR

XBO DHP for digital cinema projection | XBO品牌短弧氙灯



应用领域

- Cinema projection

产品特点

- Short arc with highest luminance for brighter screen illumination
- A lifetime of reliable performances with constant 6000 K color temperature
- Easy to maintain
- High level of arc stability
- Hot restart and instant light on screen
- Dimmable in a wide range



产品数据表

技术参数

电参数

标称电流	128 安培
标称功率	4000.00 W
电流控制范围	95...137 安培
标称电压	33.0 V

尺寸和重量

直径	60.0 mm
长度	345.0 mm
含灯头长度 (不含针脚/连接装置)	295.00 mm
输入端线缆长度	130 mm
光中心 (LCL)	123.0 mm
冷电极间隙	6.3 mm
产品重量	645.00 g
接线长度	130.0

寿命

寿命	1500 h
Service Warranty Lifetime	1900 h

更多的产品数据

阳极灯头 (标准名称)	SFaX27-14x80
阴极灯头 (标准名称)	SFc27-16/55

功能

散热	强制
燃点位置	p15/s15 ¹⁾

¹⁾ 垂直燃点位置: 正极(+)位于上端

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	07-03-2024
Primary Article Identifier	4062172114080
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.

产品数据表

Declaration No. in SCIP database	68536058-a0f0-4f39-8967-a173bfd19c5b
----------------------------------	--------------------------------------

产品数据表

安全建议

Because of their high luminance, UV radiation and internal pressure in both the hot and cold state, XBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Xenon lamps are highly explosive. When hot, xenon lamps can cause burn marks. They should only be handled when the lamp is at room temperature. Always use the protective jackets supplied when handling these lamps. When packing the lamps and when installing or removing the lamps without their protective jackets, always wear protective clothing (face shield with neck protector, protective jacket and lint-free, cut-resistant gloves). For more information see the relevant in-pack leaflets and operating instructions.

物流数据

产品代码	产品描述	包装单位 (件/单位)	尺寸 (长 x 宽 x 高)	体积	毛重
4062172114080	XBO 4000 W/DHP LL OFR	箱 1	500 mm x 204 mm x 204 mm	20.81 dm³	1440.00 g

这里所提到的产品编码代表最小订购数量。一个整件包装含有一个或多个单一产品。请您在下单时，按一个或多个整件数下单。

免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。