

HPL 93729 LL 750 W 230 V

HPL | 高光效灯泡



产品优势

- 能够实现射灯灯光的最佳利用



产品数据表

技术参数

Product information

Order reference	93729 LL
-----------------	----------


电参数

标称电压	230 V
标称功率	750.00 W
On-mode power [AGGR]	815.00 W
Energy consumption in on-mode [AGGR]	815.0 kWh/1000h

光度数据

色温	3050 K
显色指数 Ra	100
Φ_{use} value refers to luminous flux .. [AGGR]	360
Correlated color temperature CCT [AGGR]	3038 K
Useful luminous flux (Φ_{use}) [AGGR]	15595 lm
Chromaticity coordinate x [AGGR]	0.434
Chromaticity coordinate y [AGGR]	0.403

尺寸和重量



直径	19.0 mm
长度	104.0 mm
含灯头长度 (不含针脚/连接装置)	104.00 mm
光中心 (LCL)	60.3 mm
照明场	15.5*11.0 mm ^{2 1)}
灯丝直径	11.0 mm

¹⁾ 灯丝类型6-C8

产品数据表

寿命

寿命	1500 h
----	--------

更多的产品数据

灯头 (标准名称)	G9.5 w/Hsink
Lighting technology used [AGGR]	HL

功能

燃点位置	任意
------	----

认证与标准

Energy efficiency class [AGGR]	G
--------------------------------	---

特定分类

Order reference	93729 LL
ANSI编码	Other

物流数据

EAN 10 of contained light source	4052899246881
----------------------------------	---------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	22-05-2024
Primary Article Identifier	4008321090324
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

国家特殊信息

产品代码	METEL编码	SEG-No.	STK-Number	UK Org
4008321090324	OSRHPL93729LL	-	-	-
4008321090324	OSRHPL93729LL	-	-	-

产品数据表

安全建议

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (cover panel etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. Because of the heat produced only heat-resistant lamp connections (holders) may be used. Do not operate near people, or any materials that are flammable, sensitive to heat or affected by drying out. Detailed information is available on request.

物流数据

产品代码	产品描述	包装单位 (件/单位)	尺寸 (长 x 宽 x 高)	体积	毛重
4008321090324	HPL 93729 LL 750 W 230 V	纸盒 1	40 mm x 40 mm x 129 mm	0.21 dm ³	80.00 g
4008321090331	HPL 93729 LL 750 W 230 V	箱 12	174 mm x 148 mm x 145 mm	3.73 dm ³	953.00 g

这里所提到的产品编码代表最小订购数量。一个整件包装含有一个或多个单一产品。请您在下单时，按一个或多个整件数下单。

免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。