

HPL

高光效灯泡




产品优势


- 能够实现射灯灯光的最佳利用



产品系列数据表



342051_HPL 575W



342058_HPL 750W

产品系列数据表

技术参数

产品描述	Product information	电参数	光度数据	尺寸和重量		
	Order reference	标称电压	色温	直径	长度	含灯头长度 (不含针脚/连接装置)
HPL 93728 575 W 230 V	93728 HPL 575W	230 V	3200 K	19.0 mm	104.0 mm	98.00 mm
HPL 93728 575 W 240 V	93728 HPL 575W	240 V	3200 K	19.0 mm	104.0 mm	98.00 mm
HPL 93728 LL 575 W 230 V	93728 LL	230 V	3050 K	19.0 mm	104.0 mm	98.00 mm
HPL 93728 LL 575 W 240 V	93728 LL	240 /X V	3050 K	19.0 mm	104.0 mm	98.00 mm
HPL 93729 750 W 230 V	93729 HPL 750W	230 V	3200 K	19.0 mm	104.0 mm	104.00 mm
HPL 93729 750 W 240 V	93729 750W	240 V	3200 K	19.0 mm	104.0 mm	104.00 mm
HPL 93729 LL 750 W 230 V	93729 LL	230 V	3050 K	19.0 mm	104.0 mm	104.00 mm
HPL 93729 LL 750 W 240 V	93729 LL	240 V	3050 K	19.0 mm	104.0 mm	104.00 mm

产品描述	光中心 (LCL)	照明场	灯丝直径	寿命	更多的产品数据
				寿命	灯头 (标准名称)
HPL 93728 575 W 230 V	60.3 mm	9.5*11.5 mm ^{2 1)}	11.5 mm	400 h	G9.5 w/Hsink
HPL 93728 575 W 240 V	60.3 mm	9.5*11.5 mm ^{2 1)}	11.5 mm	400 h	G9.5 w/Hsink
HPL 93728 LL 575 W 230 V	60.3 mm	14.5*11.0 mm ^{2 1)}	11.0 mm	1500 h	G9.5 w/Hsink
HPL 93728 LL 575 W 240 V	60.3 mm	14.0*14.0 mm ^{2 1)}	14.0 mm	1500 h	G9.5 w/Hsink
HPL 93729 750 W 230 V	60.3 mm	7.5*11.5 mm ^{2 1)}	11.5 mm	300 h	G9.5 w/Hsink
HPL 93729 750 W 240 V	60.3 mm	7.5*11.5 mm ^{2 1)}	11.5 mm	300 h	2 pins
HPL 93729 LL 750 W 230 V	60.3 mm	15.5*11.0 mm ^{2 1)}	11.0 mm	1500 h	G9.5 w/Hsink
HPL 93729 LL 750 W 240 V	60.3 mm	15.5*11.0 mm ^{2 1)}	11.0 mm	1500 h	2 pins

产品描述	功能	特定分类	物流数据	Environmental information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
	燃点位置	ANSI编码	EAN 10 of contained light source	Date of Declaration
HPL 93728 575 W 230 V	任意	Other	4050300461816	22-05-2024
HPL 93728 575 W 240 V	任意	Other	4050300461830	22-05-2024
HPL 93728 LL 575 W 230 V	任意	Other	4008321090102	22-05-2024
HPL 93728 LL 575 W 240 V	任意	Other	4008321174444	22-05-2024

产品系列数据表

产品描述	功能	特定分类	物流数据	Environmental information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
产品描述	燃点位置	ANSI编码	EAN 10 of contained light source	Date of Declaration
HPL 93729 750 W 230 V	任意	Other	4050300654201	22-05-2024
HPL 93729 750 W 240 V	任意	Other	4052899246898	22-05-2024
HPL 93729 LL 750 W 230 V	任意	Other	4052899246881	22-05-2024
HPL 93729 LL 750 W 240 V	任意	Other	4052899246911	22-05-2024

产品描述	Primary Article Identifier	Candidate List Substance 1	Declaration No. in SCIP database
HPL 93728 575 W 230 V	4050300461816	No declarable substances contained	No declarable substances contained
HPL 93728 575 W 240 V	4050300461830	No declarable substances contained	No declarable substances contained
HPL 93728 LL 575 W 230 V	4008321090102	No declarable substances contained	No declarable substances contained
HPL 93728 LL 575 W 240 V	4008321174444	No declarable substances contained	No declarable substances contained
HPL 93729 750 W 230 V	4050300654201	No declarable substances contained	No declarable substances contained
HPL 93729 750 W 240 V	4050300654225 4052899246898	No declarable substances contained	No declarable substances contained
HPL 93729 LL 750 W 230 V	4008321090324	No declarable substances contained	No declarable substances contained
HPL 93729 LL 750 W 240 V	4008321174468 4052899246911	No declarable substances contained	No declarable substances contained

1) 灯丝类型6-C8

产品系列数据表

安全建议

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (cover panel etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. Because of the heat produced only heat-resistant lamp connections (holders) may be used. Do not operate near people, or any materials that are flammable, sensitive to heat or affected by drying out. Detailed information is available on request.

应用建议

更多详细应用信息和图形,请参阅产品数据表。

免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。