OSRAM

Cube MX240-CB



ECE certified - ECE R7R112

The necessary tests and approvals were carried out and an ECE type approval was granted2)ECE reference number: 50



Combo Beam

Designed for both: far-field and near-field illumination. For widespread illumination in the near field and spot illumination in the far field.



Light beam up to 430 m length

See and be seen with OSRAM



on-road & off-road

Versatile applicable and flexible in use.On-road & off-road, in terrain, at work and in the spare time.



Bringing light to life with OSRAM LEDriving driving and working lights

Considerable foresight on dark country roads, forest paths, off the beaten tracks, off-road and on-road- this can be achieved with the OSRAM LEDriving Cube MX240-CB. With its 16 powerful, high-performance long-life LEDs, the OSRAM LEDriving Cube MX240-CB has a range of up to 430 meters and thus offers the driver impressive foresight on-road and off-road. Even in dim light and reduced visibility due to external environmental influences, the OSRAM LEDriving Cube MX240-CB with up to 6000 Kelvin can provide conditions similar to daylight. The power package with up to 4000 lumens of luminosity scores with highest optical efficiency and homogeneous light distribution. This results in the possibility of an improved view for you and the improved visibility of your vehicle by other road users, and consequently also increased safety on-road and off-road. Whether on-road or off-road - The OSRAM LEDriving Cube MX240-CB impresses with its powerful performance and a long service life with up to 5000 hours. Versatile applicable, it defies numerous environmental influences and, thanks to high-quality materials such as the aluminum housing and the stable polycarbonate lens, it is particularly light and at the same time robust and resistant. The OSRAM LEDriving Cube MX240-CB has been tested and validated with the IP-Protection Class IP69K in our DIN certified environmental simulation laboratory for extreme external influences regarding water, dust, impacts, heat, cold and permanent vibration. The integrated driver and the thermal management system regulate the temperature of the LED Lightbar and can thus prevent damage from overheating. The polarity protection inhibits the wrong polarity of the voltage supply and can thus prevent possible damage by automatically switching off the LEDs. On-road and off-road, the OSRAM LEDriving Cube MX240-CB is an effective and efficient addition to your vehicle. No registration or entry in the vehicle documents is necessary for these ECE-certified LED driving lights2).ECE reference number: 50The OSRAM LEDriving Cube MX240-CB can be attached to cars, trucks, agricultural machinery, farm machinery, commercial vehicles, construction vehicles, caravans, off-road vehicles and quads2). The OSRAM LEDriving Cube MX240-CB is versatile applicable and flexible in use.2) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed.

技术参数

Product information

Order reference	LEDDL113-CB
Application (Category and Product specific)	Additional high beam and position light

电参数

标称电压	12/24 V
标称功率	70/1,5 W
测试电压	13.5 V

光度数据


光通量	4000 lm
色温	6000 K
Light distance at 1lx	430 m

LED 模块信息

模块LED颗粒数	10/16

尺寸和重量





产品重量	3380.00 g
长度	241 mm
宽度	169 mm
高度	134 mm

寿命

使用寿命 Tc	5000 h
Guarantee	5 年

更多的产品数据



光强分部图

光源连接头	Open wire
产品说明	Beam Pattern: Combo

功能

Technology	LED ¹⁾

¹⁾ Light-emitting diode application

认证与标准

标准	ECE R10, R112, R7
认证标志 – 认证	E4 认证
防护类型	IP69K
ECE reference number	50

特定分类

物流数据

商品编码	85122000900

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Date of Declaration	28-02-2024
Primary Article Identifier	4062172154017
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	d44b701c-22d2-49ff-a9f5-29a7286f1014

物流数据

产品代码	产品描述	包装单位(件/单位)	尺寸(长 x 宽 x 高)	体积	毛重
4062172154017	Cube MX240-CB	纸盒 1	302 mm x 274 mm x 162 mm	13.41 dm³	3880.00 g
4062172154024	Cube MX240-CB	箱 2	320 mm x 292 mm x 357 mm	33.36 dm ³	8372.00 g

这里所提到的产品编码代表最小订购数量。一个整件包装含有一个或多个单一产品。请您在下单时,按一个或多个整件数下 单。

下载数据

	文件
7	User instruction LEDriving Cube MX240-CB
D	电影应用 OSRAM Quality Testing LEDriving working and driving lights (EN)
D	电影应用 OSRAM LEDdriving and working lights Imagefilm (EN)
D	电影应用 LEDriving Driving and Working Lights Reference Video (EN)
D	电影应用 Working and Driving Lights Amarok Winter
D	Video Light is Quality -OSRAM LEDriving Driving and Working Lights Quality Tests (EN)
D	Video OSRAM LEDriving driving and working lights: The night doesn't stand a chance
D	Video OSRAM LEDriving driving and working lights in action - From on road to off road applications (EN)



Video

Reference Number made easy - Making sure your LEDriving Driving Lights are legal on public roads



360 Degree Image

LEDriving Round MX260-CB

Legal advice:

The installation of the OSRAM LEDriving Cube MX240-CB is fully ECE compliant and therefore registration free. This does not include individual custom requirements of countries, in addition to the standardized ECE certification of the product.

- 1) Precise terms and conditions at: www.osram.com/am-guarantee
- 2) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed.

Refer to www.osram.com/am-guarantee for precise conditions

应用建议

更多详细应用信息和图形,请参阅产品数据表。

免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。

OSRAM