

# XENARC NIGHT BREAKER LASER (NEXT GEN) D2S

最明亮的欧司朗氙气灯



Up to 220% more brightness<sup>1), 2)</sup>

照射距离更远，驾驶人员可以反应更迅速，与最低法律标准相比



照路距离高达250米

具有更高能见度



Up to 20% whiter light<sup>1)</sup>

时尚外观，与最低法律标准相比



For more customer satisfaction

3 year guarantee, refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee) for precise conditions



欧司朗功率最强的氙气灯

XENARC NIGHT BREAKER LASER is the brightest OSRAM xenon light. This powerful lamp with efficient xenon technology ensures a better visibility on the road: up to 220% more brightness compared to the minimum legal standard. More light allows to see further and therefore react sooner. Added to this is the up to 250 meter long beam and up to 20% whiter light for more modern look (compared to the minimum legal standard). Discover the pure performance of XENARC NIGHT BREAKER LASER - the most powerful xenon light from OSRAM, available in D1S, D2S, D3S and D4S. Please note: XENARC lamp change is recommended to be carried out by a professional and in pairs.<sup>1)</sup> Compared to minimum ECE R98/R99 requirements<sup>2)</sup> D3S, D4S

## 产品数据表

### 技术参数

#### Product information

Product legal advice 1	1) Compared to minimum ECE R98/R99 requirements
Product legal advice 2	2) D3S, D4S

#### 电参数

功率输入	35 W
标称电压	85.0 V
标称功率	35.00 W
输入功率容许偏差	±3 %
测试电压	13.5 V

#### 光度数据

光通量	3200 lm
光通量容许偏差	±15 %

#### 尺寸和重量

长度	77.3 mm
直径	9 mm
产品重量	16.10 g

#### 寿命

Lifespan B3	1500 h
使用寿命 Tc	3000 h

#### 更多的产品数据

灯头 (标准名称)	P32d-2
-----------	--------

#### 功能

Technology	HID
------------	-----

#### 认证与标准

ECE 分类	D2S <sup>1)</sup>
认证标志 - 认证	E1 认证

<sup>1)</sup> 仅可使用经过认证的电子控制装置运行

#### Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
---

## 产品数据表


Date of Declaration	08-03-2024
Primary Article Identifier	4052899631298   4052899631335
Declaration No. in SCIP database	In work

## 物流数据

产品代码	产品描述	包装单位 (件/单位)	尺寸 (长 x 宽 x 高)	体积	毛重
4052899631298	XENARC NIGHT BREAKER LASER D2S	塑料盒 2	114 mm x 49 mm x 106 mm	0.58 dm <sup>3</sup>	124.00 g
4062172313612	XENARC NIGHT BREAKER LASER D2S	箱 4	122 mm x 106 mm x 121 mm	1.56 dm <sup>3</sup>	328.00 g
4062172313629	XENARC NIGHT BREAKER LASER D2S	箱 48	371 mm x 256 mm x 232 mm	22.03 dm <sup>3</sup>	4192.00 g
4052899631335	XENARC NIGHT BREAKER LASER D2S	纸盒 1	53 mm x 46 mm x 93 mm	0.23 dm <sup>3</sup>	36.00 g
4062172313704	XENARC NIGHT BREAKER LASER D2S	箱 4	115 mm x 101 mm x 103 mm	1.20 dm <sup>3</sup>	176.00 g
4062172313711	XENARC NIGHT BREAKER LASER D2S	箱 48	371 mm x 256 mm x 232 mm	22.03 dm <sup>3</sup>	2368.00 g

这里所提到的产品编码代表最小订购数量。一个整件包装含有一个或多个单一产品。请您在下单时，按一个或多个整件数下单。

## 下载数据

文件
 电影应用 Installation Video Xenarc Night Breaker Laser Opel Zafira (EN)

### 安全建议

XENARC lamps should be replaced by a qualified mechanic.

This product must only be operated with approved electronic control gear.

### 法律建议

Light output compared to the minimum ECE R98/99 requirements

This product must only be operated with approved electronic control gear

XENARC lamps should be replaced by a qualified mechanic

Reduced UV emission | For projection headlights | ECE approval and DOT label

± 450 lm

## 产品数据表

### 应用建议

更多详细应用信息和图形,请参阅产品数据表。

### 免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。

# OSRAM